



Dust Blower LXT®, 18V, 200 m/s, 1,1 m³/ min

DAS180Z



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Max. Air Velocity	200 m/s
Blowing force	1,1 / 1,7 / 2,3 / 2,8 N
Air volume	0,6 / 0,8 / 1,0 / 1,1 m ³ /min
Max. sealed suction	103 mbar
Max Pressure	0,297 bar
Anti-Restart Function (NVR Switch)	✓
Continuous Use 18V / 6.0 Ah Battery	55 / 30 / 20 / 15 min
Sound Power Level (L _{WA})	90 dB(A)
Sound Pressure Level (L _{pA})	82 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Tool weight with battery	1,2 - 1,7 kg

User benefits

- Variable speed control by trigger
- 4 stage air volume; selectable according to your application
- Brushless maintenance-free and long-life motor
- Battery capacity warning function automatically notifies the user about reduction in battery capacity with the decrease of illuminance
- Battery protection system automatically shuts off power when the battery level is low

EAN 0088381779975

Link to product - www.makita.com



Related products

■ Standard AC

191X11-1
Narrow Nozzle

191X15-3
Blower Nozzle

191X19-5
Wide Nozzle

191X13-7
Nozzle for cleaning filter

191X17-9
Nozzle for inflating

■ Optional AC

191X27-6
Suction Nozzle Attachment 65 Set

■ Other

User manual

Parts drawing