

Combi Drill LXT®

DHP453Z

18V • 42 Nm • 0 – 1 300 min⁻¹

Combi drill with hammer action for demanding amateur builders

For screwdriving and drilling with or without hammer action, two power settings. Max. torque of 42 / 27 Nm. Suitable for light professional use or demanding amateur use



LXT

Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
No load speed	0 - 400 / 1300 min ⁻¹
Max. fastening torque Hard/Soft	42 / 27 Nm
Torque setting	16
Max Torque	48 Nm
Impacts per Minute (IPM)	0 - 6000 / 19500 min ⁻¹
Drilling Capacity Wood (Auger Bit)	38 mm
Drilling Capacity Wood (Self-feed bit)	38 mm
Max. Drilling Diameter in Masonry	13 mm
Max. Drilling Diameter in Steel	13 mm
Drilling Capacity Flat bit	38 mm
Drilling Capacity Hole Saw	51 mm
Drill Chuck Capacity	1,5 - 13 mm
Electronic brake	✓
Sound Power Level (L _{WA})	94 dB(A)

User benefits

- With impact mode, the tool can be used for drilling stone materials.
- All metal gear construction ensures high transmission durability
- Single sleeve keyless chuck enables easy bit installation/removal with one hand
- The rubber coating on the handle ensures a firm working grip
- Battery protection circuit protects against overloading, over-discharging and over-heating

EAN 0088381661287

Link to product - www.makitauk.com



Related products

■ **Standard AC**

784636-0

Double Ended Torsion Bit, Ph2, 65



■ **Other**

User manual

Parts drawing