



Combi Drill LXT®

DHP482RTJ

18V • 62 Nm • 0 – 1 900 min⁻¹

Powerful general-use combi drill with hammer action for professionals

An efficient drill for professional screwdriving and drilling with or without hammer action, two power settings. Max. torque of 62 / 36 Nm. A versatile tool for fitters, builders and maintenance staff. Integrated LED light. Two 5.0 Ah batteries and a charger in Makpac case included.



LXT

Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 600 / 1900 min ⁻¹
Max. fastening torque Hard/Soft	62 / 36 Nm
Torque setting	21
Max Torque	64 Nm
Impacts per Minute (IPM)	0 - 9000 / 28500 min ⁻¹
Max. Drilling Diameter in Concrete	13 mm
Max. Drilling Diameter in Masonry	13 mm
Max. Drilling Diameter in Steel	13 mm
Drilling Capacity Wood (Auger Bit)	38 mm
Drilling Capacity Wood (Self-feed bit)	51 mm
Drilling Capacity Flat bit	38 mm
Drilling Capacity Hole Saw	51 mm
Driving Shank	1/2"-20UNF "

EAN 0088381813631

Link to product - www.makita.uk.com

User benefits

- Highly efficient and compact machine for professional use
- Battery protection system automatically shuts off power when the battery level is low
- Optimal handle design
- LED light illuminates the work site
- Ergonomic handle for easy manoeuvring



Related products

Standard AC

346317-0
Belt Hook



821550-0
Makpac case (2)



Standard MA

BL1850B (2x)
Battery LXT® 5,0 Ah



Optional AC

196311-0
Keyless Drill Chuck, 13 mm



251314-2
Truss Head Screw M4*12, Td140D



346317-0
Belt Hook



784637-8
Screw Bit, Ph2 – S6, 45 Mm, Double



821550-0
Makpac case (2)



837916-4
MakPac (2) Inlay



D-72877
Drill bit set T.C.T, 5 pcs



Other

User manual

Parts drawing