

Rotary Hammer LXT® DHR202Z

18V • SDS-Plus • 20 mm • 2.0 J

Professional three-mode rotary hammer

An efficient rotary hammer for SDS-Plus bits with an anti-vibration handle. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 – 1 100 min-1. Impact energy of 2.0 J and max. drilling capacity of 20 mm in concrete. Tool only, battery and charger not included.





Technical specifications

Voltage LXT Nominal Battery Voltage Battery Chemistry (Ni-Cd / Ni-MH / Li- ion)	√ 18 V Li-ion
No load speed	0 - 1100 min ⁻¹
Impacts per Minute (IPM)	0 - 4000 min ⁻¹
Max. Drilling Diameter in Wood Max. Drilling Diameter in Concrete Max. Drilling Diameter in Steel Optimum Drilling Diameter Range in Concrete	26 mm 20 mm 13 mm 4 - 12 mm
Impact Energy Drilling diameter with TCT core bit Adapted for SDS-PLUS bits Electronic brake Sound Power Level (L _{WA})	1,9 J 54 mm √ √ 99 dB(A)

User benefits

- Battery protection system automatically shuts off power when the battery level is low
- LED light illuminates the work site
- 3-Mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only" for multiple applications
- Reversing switch
- · Reversing switch is conveniently located
- Compact and lightweight for reduced operator fatigue
- One touch sliding chuck enables quick and easy bit changes



EAN 0088381658119

Link to product - www.makitauk.com

Related products

Standard AC

324219-0 Depth Gauge

Optional AC

193472-7 Dust extraction set Ø 25 / 31 mm

837634-4 MakPac (3) Inlay

D-74136 Drill Bit Set T.C.T, SDS-PLUS, 4 pcs



821551-8 Makpac case (3)



D-16368 Chisel set SDS-PLUS, 5 pcs



User manual

Parts drawing