

# Recipro Saw LXT®

## DJR186

18V • 0 – 2 800 min<sup>-1</sup> • 32 mm

### Efficient basic reciprocating saw

An efficient reciprocating saw for spark-free cutting of metal and demolition work. Stroke length of 32 mm and stroke rate of 0 – 2 800 min<sup>-1</sup> with continuous control from the switch. Quick-release blade attachment.



### Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Strokes per Minute (SPM)	0 - 2800 min <sup>-1</sup>
Length of Stroke	32 mm
Max. Cutting Capacity in Wood (90°)	255 mm
Max. Cutting Capacity in Steel Pipe	130 mm
Sound Power Level (L <sub>WA</sub> )	95 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	84 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Tool weight with battery	3,5 - 3,8 kg
Product Dimensions (L x W x H):	486 x 81 x 223 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Vibration Level, Cutting Boards	13,0 m/s <sup>2</sup>
Vibration Uncertainty (K Factor), Cutting Boards	1,5 m/s <sup>2</sup>

### User benefits

- Compact and lightweight for reduced operator fatigue
- Slim design with rubberised grip for comfort
- Tool-less blade change and shoe adjustment
- eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- Battery protection system automatically shuts off power when the battery level is low

Link to product - [www.makita.com](http://www.makita.com)



# Related products

## ■ Optional AC

**B-10394**

Reciprosaw Blade 305 x 1,5 mm



**B-44432**

Reciprosaw Blade Set 6 pcs



**B-44448**

Reciprosaw Blade Set 6 pcs



**P-04880**

Reciprosaw Blade 150 x 1,4 mm



---

## ■ Other

[User manual](#)

[Parts drawing](#)