

## Impact driver LXT®

# DTD157Z

18V • 1/4" • 140 Nm • 0 – 3 000 min<sup>-1</sup>

**Extra-compact brushless impact driver with assist mode and three power settings for quick driving.**

A compact and light impact wrench with a hex. 1/4" drive shank. A compact tool with a max. torque of 140 Nm. 3-mode operation for A-mode / Hard mode / Soft mode for multiple applications. Handy LED light. Tool only, battery and a charger not included.



### Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
No load speed	0 - 1300 / 3000 min <sup>-1</sup>
Max Fastening Torque Impact Drill	140 Nm
Tightening Capacity Standard Bolt	M5 - M14
Impacts per Minute (IPM)	0 - 2000 / 4100 min <sup>-1</sup>
Driving Shank	1/4 "
Sound Power Level (L <sub>WA</sub> )	106 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	98 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Tool weight with battery	1,2 - 1,5 kg
Product Dimensions (L x W x H):	133 x 81 x 232 mm
Vibration Level, Impact Tightening of Fasteners of the Maximum Capacity of the Tool	11,5 m/s <sup>2</sup>
Vibration Uncertainty (K Factor),	1,5 m/s <sup>2</sup>

**EAN 0088381738576**

Link to product - [www.makita.com](http://www.makita.com)

### User benefits

- Brushless motor is electronically controlled to optimise battery energy use for longer run time per charge
- LED light illuminates the work site
- eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- Anti wobbling bit structure
- Battery protection system automatically shuts off power when the battery level is low



# Related products

## ■ Standard AC

346317-0  
Belt Hook



---

## ■ Optional AC

266622-8  
Truss Head Screw M4 X 12



346317-0  
Belt Hook



---

## ■ Other

[User manual](#)

[Parts drawing](#)