



# Angle Impact Driver LXT®

## DTL061Z

18V • 1/4" • 60 Nm • 0 – 2 000 min<sup>-1</sup>

**Angle impact wrench for tight spaces**

A compact and light 1/4" angle impact wrench. An angle head height of 53 mm makes this tool an ideal choice for tight spaces. A long paddle switch and handy LED light for added comfort. Tool only, battery and charger not included.



### Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 2000 min <sup>-1</sup>
Max Fastening Torque Impact Drill	60 Nm
Tightening Capacity Standard Bolt	M4 - M12
Impacts per Minute (IPM)	0 - 3000 min <sup>-1</sup>
Driving Shank	1/4 "
Sound Power Level (L <sub>WA</sub> )	102 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	94 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Tool weight with battery	1,4 - 2,0 kg
Product Dimensions (L x W x H):	387 x 78 x 116 mm
Angle length	53 mm

### User benefits

- Large paddle switch trigger for easy operation
- The rubber coating on the handle ensures a firm working grip
- LED light illuminates the work site
- Ideal for working in tight spaces and overhead applications
- Quick mount for 1/4 "screwdriver
- Electric brake for maximum productivity and increased operator safety
- Variable speed control dial enables user to match the speed to the application for greater versatility
- Battery protection system automatically shuts off power when the battery level is low

**EAN 0088381664240**

[Link to product - www.makita.com](http://www.makita.com)



# Related products

## ■ Standard AC

**251314-2**

Truss Head Screw M4\*12, Td140D

**346317-0**

Belt Hook

---

## ■ Optional AC

**251314-2**

Truss Head Screw M4\*12, Td140D

**346317-0**

Belt Hook

**821550-0**

Makpac case (2)

**837644-1**

MakPac (2) Inlay

**B-42961**

Threaded Rod Socket M6

**B-42977**

Threaded Rod Socket M8

**B-42983**

Threaded Rod Socket M10

---

## ■ Other

**User manual**

**Parts drawing**