



Angle Grinder

GA4530R/1

750 W • 115 mm • 11 000 min⁻¹

Mini-grinder with anti-restart feature for cutting and grinding

Grinder with anti-restart feature to prevent accidental and unexpected restart of the machine for improved safety. Slim motor housing with small circumference of 179 mm for improved grip. High quality motor with excellent heat resistance.

Technical specifications

Continuous Input Power 240V	720 W
No load speed	11000 min ⁻¹
Max. Depth of Cut	30 mm
Spindle Thread	M14
Bore Size (Arbor Diameter)	22,23 mm
Disc Diameter	115 mm
Anti-Restart Function (NVR Switch)	✓
Sound Power Level (L _{WA})	96 dB(A)
Sound Pressure Level (L _{pA})	88 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level, Disc Sanding	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor), Disc Sanding	1,5 m/s ²
Vibration Level, Surface Grinding	7,5 m/s ²
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s ²

EAN 0088381808514

Link to product - www.makitauk.com

User benefits

- Anti-restart function minimises accidental start-up
- The engine compartment labyrinth design protects the engine from the impurities that come with the cooling air
- Spindle lock for easy wheel changes
- Spiral bevel gears for smoother rotations, quieter gear noise and a more efficient transfer of energy



Related products

■ Standard AC

153489-2

Grip complete 125 mm



741471-9

Depressed Center Wheel 115-36

782423-1

Lock nut wrench 35



A-80927

Grinding wheel 115 x 6 mm, A36P,



■ Other

User manual

Parts drawing