



Percussion Drill

HP1640/2

680 W • 16 mm • 0 – 2 800 min⁻¹

Compact drill with hammer and drive functions

Compact 680 W percussion drill with a masonry drilling capacity of 16 mm. A slimline frame and large switch for added usability. With rugged aluminium housing for gear drive. 13 mm quick action drill chuck.

Technical specifications

Continuous Input Power 240V	680 W
Max Output Power	600 W
No load speed	0 - 2800 min ⁻¹
Impacts per Minute (IPM)	0 - 44800 min ⁻¹
Max. Drilling Diameter in Concrete	16 mm
Max. Drilling Diameter in Masonry	16 mm
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	30 mm
Drilling Capacity Wood (Auger Bit)	30 mm
Drilling Capacity Wood (Self-feed bit)	60 mm
Drilling Capacity Hole Saw	60 mm
Drill Chuck Capacity	1,5 - 13 mm
Sound Power Level (L _{WA})	106 dB(A)
Sound Pressure Level (L _{pA})	98 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)

User benefits

- Ergonomic soft grip handle provides increased comfort
- Same speed and torque in both directions with reverse gear
- Variable speed control dial enables user to match the speed to the application for greater versatility
- Double insulated

EAN 0088381096614

Link to product - www.makita.uk.com



Related products

Standard AC

324219-0

Depth Gauge

Other

User manual

Parts drawing