



# Rotary Hammer

## HR2630T/1

800 W • SDS-PLUS • 26 mm • 2.4 J

### Three-mode rotary hammer with quick-change chuck

A compact and efficient rotary hammer compatible with SDS-PLUS bits. Suitable for impact and unstressed drilling, plus chipping. Motor capacity of 800 W and speed can be adjusted between 0 and 1 200 min<sup>-1</sup> from a switch. Impact energy of 2.4 J and optimal drilling range of 8 – 18 mm in concrete. Max. drilling capacity of 26 mm in concrete.

### Technical specifications

Power Supply Cord	2,5 m
Continuous Input Power 240V	800 W
Max Output Power	550 W
No load speed	0 - 1200 min <sup>-1</sup>
Impacts per Minute (IPM)	0 - 4600 min <sup>-1</sup>
Max. Drilling Diameter in Wood	32 mm
Max. Drilling Diameter in Concrete	26 mm
Max. Drilling Diameter in Steel	13 mm
Optimum Drilling Diameter Range in Concrete	4 - 18 mm
Impact Energy	2,4 J
Drilling diameter with TCT core bit	68 mm
Adapted for SDS-PLUS bits	✓
Sound Power Level (L <sub>WA</sub> )	101 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	93 dB(A)

### User benefits

- Same speed and torque in both directions with reverse gear
- The rubber coating on the handle ensures a firm working grip
- Torque limiter stops rotation if bit jams for increased operator safety and enhanced motor protection
- 3-Mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only" for multiple applications
- Depth gauge for increased drilling consistency
- Quick-change chuck for quick changeover to wood and metal drill bits
- Variable speed trigger allows operator to adjust speed based on materials or application

**EAN 0088381687386**

Link to product - [www.makitauk.com](http://www.makitauk.com)



# Related products

## ■ Standard AC

**194079-2**

Quick Change Drill Chuck 13 mm,



**331886-4**

Depth Gauge

**824916-3**

Plastic Carrying Case



## ■ Other

**User manual**

**Parts drawing**