

Circular Saw CXT®

HS301DZ

12Vmax • 1 500 min⁻¹ • 85 mm

Small circular saw for light use

A small and light hand-held circular saw for small jobs. A speed of 1 500 min⁻¹, and blade diameter of 85 mm that offers a maximum cutting depth of 25.5 mm. Dust removal function helps keep cut line visible. Tool only, battery and charger not included.



Technical specifications

CXT Battery	✓
Nominal Battery Voltage	12 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	1500 min ⁻¹
Max. Cutting Depth at 90°	25,5 mm
Max. Cutting Depth at 45°	16,5 mm
Max. Bevel Range (Right)	0 - 45 °
Blade Diameter	85 mm
Bore Size (Arbor Diameter)	15 mm
Sound Power Level (L _{WA})	97 dB(A)
Sound Pressure Level (L _{pA})	86 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Tool weight with battery	1,6 - 1,7 kg
Vibration Level, Cutting Wood	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor),	1,5 m/s ²

User benefits

- Cutting depth adjustment
- Tilting base for bevel cuts from 0° - 45°
- Built-in dust blower clears the line of cut for greater accuracy
- The rubber coating on the handle ensures a firm working grip
- Battery protection system automatically shuts off power when the battery level is low

EAN 0088381804943

Link to product - www.makitauk.com



Related products

Standard AC

783202-0
Hex Wrench 4Mm



Optional AC

164095-8
Parallel Guide



452237-9
Dust nozzle Ø 25 / 31 mm



783202-0
Hex Wrench 4Mm



821550-0
Makpac case (2)



837662-9
MakPac (2) Inlay



838315-3
MakPac Type 2 Inlay



B-32932
Circular Saw Blade, Specialized



B-33819
Circular Saw Blade, Specialized



Other

User manual

Parts drawing