

Reciprocating Saw CXT®

JR105DZ

12V max • 0 – 3 300 min⁻¹ • 13 mm

Compact reciprocating saw for light use, also accepts jigsaw bits

A straight-framed light and small reciprocating saw offers access to tight places. Two separate switches enable diverse working postures. Stroke length of 13 mm, stroke rate can be adjusted between $0 - 3\,300$ min-1 from a switch. LED light. Tool only, battery and charger not included.





Technical specifications

CXT Battery Nominal Battery Voltage Battery Chemistry (Ni-Cd / Ni-MH / Li- ion) Strokes per Minute (SPM)	√ 12 V Li-ion 0 - 3300 min ⁻¹
Length of Stroke Max. Cutting Capacity in Wood (90°) Max. Cutting Capacity in Steel Pipe Sound Power Level (L _{WA})	13 mm 50 mm 50 mm 89 dB(A)
Sound Pressure Level (L_{pA})	81 dB(A)
Noise Uncertainty (K Factor) Vibration Level, Cutting Boards Vibration Uncertainty (K Factor), Cutting Boards Vibration Level, Cutting Wooden Beam Vibration Uncertainty (K Factor), Cutting Wooden Beam	3 dB(A) 8,0 m/s ² 1,5 m/s ² 8,0 m/s ² 1,5 m/s ²

User benefits

- Two different operating switches for versatile working
- Accepts both Recipro and Jig saw blades
- Ideal for working in tight spaces and overhead applications
- LED light illuminates the work site
- The rubber coating on the handle ensures a firm working grip
- Battery protection system automatically shuts off power when the battery level is low



EAN 0088381800907

Link to product - www.makitauk.com

Related products

Standard AC

195776-3 Accessory Set 783201-2 Hex Wrench 3Mm



821549-5 Makpac case (1)



838313-7 Makpac Type 1 Inner tray



User manual

Parts drawing

T