

Reciprocating Saw JR3051TK/1

1 200 W • 0 - 3 000 min⁻¹ • 30 mm

A basic reciprocating saw for spark-free cutting of metal and demolition work. An efficient 1 200 W motor, stroke length of 30 mm and stroke rate of 0 – 3 000 min⁻¹ with continuous control from the switch. Quick-release blade attachment.

Technical specifications

Power Supply Cord Continuous Input Power 240V Strokes per Minute (SPM)	2,5 m 1200 W 0 - 3000 min ⁻¹
Length of Stroke Max. Cutting Capacity in Wood (90°) Max. Cutting Capacity in Steel Pipe Sound Power Level (L _{WA})	30 mm 255 mm 130 mm 99 dB(A)
Sound Pressure Level (L _{pA})	88 dB(A)
Noise Uncertainty (K Factor) Vibration Level, Cutting Boards Vibration Uncertainty (K Factor), Cutting Boards Vibration Level, Cutting Wooden Beam Vibration Uncertainty (K Factor),	3 dB(A) 19,5 m/s ² 1,5 m/s ² 19,5 m/s ² 1,5 m/s ²
Cutting Wooden Beam Weight Without Cable	3,3 kg

User benefits

- Tool-less blade change for fast blade installation and removal
- Compact and lightweight for reduced operator fatigue
- Soft grip handle provides increased comfort on the job
- Variable speed trigger for precise cutting in a wide variety of applications
- Large 2-finger trigger for added convenience



EAN 0088381891912

Link to product - www.makitauk.com



Related products

Standard AC

194253-2

Recipro Saw Blade Set

Total Total Control

412670-7 Band

821795-0

Plastic Carrying Case





Other

User manual

Parts drawing