

# Reciprocating Saw MT-Series

## M4501

1 010 W • 0 – 2 800 min<sup>-1</sup> • 28 mm

A reliable recipro saw for metal cutting and demolition.

Reciprocating saw with 1 010 W motor for non-sparking metal cutting and demolition. Quick blade attachment and 28 mm stroke length makes working faster.



### Technical specifications

Continuous Input Power 240V	1010 W
Strokes per Minute (SPM)	0 - 2800 min <sup>-1</sup>
Length of Stroke	28 mm
Max. Cutting Capacity in Wood (90°)	255 mm
Max. Cutting Capacity in Steel Pipe	130 mm
Sound Power Level (L <sub>WA</sub> )	98 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	87 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Weight Without Cable	3,2 kg
Vibration Level, Cutting Boards	19,5 m/s <sup>2</sup>
Vibration Uncertainty (K Factor), Cutting Boards	1,5 m/s <sup>2</sup>
Product Dimensions (L x W x H):	457 x 98 x 170 mm
Vibration Level, Cutting Wooden Beam	22,0 m/s <sup>2</sup>
Vibration Uncertainty (K Factor), Cutting Wooden Beam	2,0 m/s <sup>2</sup>

**EAN 0088381816359**

Link to product - [www.makita.com](http://www.makita.com)

### User benefits

- Variable speed trigger for precise cutting in a wide variety of applications
- Tool-less blade change and shoe adjustment
- Soft grip handle provides increased comfort on the job
- Built-in dust blower clears the line of cut for greater accuracy
- Double insulated



# Related products

## ■ Other

User manual

Parts drawing