

Radio CXT® / LXT® / XGT®

MR003G

12V - 40V max

Dual Power Sources: AC or Makita batteries.

Capable of Receiving DAB / DAB+ (Digital Audio Broadcasting). Sturdy radio with IP65 protection rating. Can be used with 12V, 18V and 40V batteries or mains power. (Batteries are not included).



Technical specifications

Nominal Battery Voltage	12 / 14,4 / 18 / 40 V
CXT Battery	✓
Voltage LXT	✓
Voltage XGT	✓
Frequency Range FM	87,5 - 108 MHz
Frequency Range DAB+	174,928 - 239,200 MHz
Continuous Use 18V / 2.0 Ah Battery	11 h
Continuous Use 18V / 4.0 Ah Battery	22 h
Continuous Use 18V / 5.0 Ah Battery	29 h
Continuous Use 18V / 6.0 Ah Battery	35 h
International Protection Class (IP)	IP65
Tool weight with battery	4,6 - 5,4 kg
Product Dimensions (L x W x H):	280 x 171 x 298 mm
Continuous Use 14.4V / 3.0 Ah Battery	13 h
Continuous Use 18V / 3.0 Ah Battery	16 h
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion

Link to product - www.makita.com



Related products

■ Other

User manual

Parts drawing