

# Impact Driver XGT®

## TD002G

1/4", 220 Nm, 0 – 3 700 min<sup>-1</sup>

Model TD002G is a cordless impact driver powered by 40Vmax XGT® Li-Ion battery

Equipped with a new mechanism "dual spring technology", TD002G enables more comfortable operation in a wide range of applications from light-duty screw tightening to heavy-duty metal fastening



### Technical specifications

Nominal Battery Voltage	40 V
Voltage XGT	✓
Brushless Motor	✓
No load speed	0 - 1100 / 2100 / 3200 / 3700 min <sup>-1</sup>
Max Fastening Torque Impact Drill	20 / 50 / 170 / 220 Nm
Tightening Capacity Standard Bolt	M5 - M16
Capacity machine screw	M4 - M8
Tightening Capacity High Tensile Bolt	M5 - M14
Impacts per Minute (IPM)	0 - 1400 / 2600 / 3600 / 4600 min <sup>-1</sup>
Sound Power Level (L <sub>WA</sub> )	105 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	94 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Tool weight with battery	1,7 - 2,9 kg

### User benefits

- Ergonomic soft grip handle provides increased comfort
- Electric brake for maximum productivity and increased operator safety
- eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- Battery protection circuit protects against overloading, over-discharging and over-heating
- Constant speed control maintains fastening torque by minimising the rotation speed reduction caused by decreased battery capacity

Link to product - [www.makita.com](http://www.makita.com)



# Related products

## ■ Other

User manual

Parts drawing