

Drill Driver LXT®

DDF482Z

18V • 62 Nm • 1 900 min⁻¹

Powerful general-use drill for screwdriving and drilling

An efficient tool with two speed ranges for screwdriving and drilling for professional use. Max. torque of 62 / 36 Nm. A versatile tool for fitters, builders and maintenance staff. Integrated LED light. Tool only, battery and charger not included.



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 600 / 0 - 1900 min ⁻¹
Max. fastening torque Hard/Soft	62 / 36 Nm
Torque setting	21
Max Torque	64 Nm
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	38 mm
Drilling Capacity Wood (Auger Bit)	38 mm
Drilling Capacity Wood (Self-feed bit)	60 mm
Driving Shank	1/2"-20UNF "
Drill Chuck Capacity	1,5 - 13 mm
Product net weight	1,1 kg
Sound Pressure Level (L _{pA})	78 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)

User benefits

- The rubber coating on the handle ensures a firm working grip
- All metal gear construction ensures high transmission durability
- LED light illuminates the work site
- Mechanical 2-speed gearing; High speed mode for speedy drilling in light duty applications; Low speed mode for heavy duty applications requiring high torque
- eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- Battery protection system automatically shuts off power when the battery level is low
- Highly efficient and compact machine for professional use

EAN 0088381699013

Link to product - www.makita.com



Related products

Standard AC

346317-0
Belt Hook



Optional AC

196311-0
Keyless Drill Chuck, 13 mm



251314-2
Truss Head Screw M4*12, Td140D



346317-0
Belt Hook



784637-8
Screw Bit, Ph2 – S6, 45 Mm, Double



D-72833
Metal Drill Bit set HSS-Tin, 2 - 8 mm,



Other

[User manual](#)

[Parts drawing](#)