

# Drill Driver LXT®

## DDF486Z

18V • 125 Nm • 0 – 2 100 min<sup>-1</sup>

**A powerful, brushless general-use drill for screwdriving and drilling.**

An efficient brushless tool with two speed ranges for screwdriving and drilling for professional use. Max. torque of 130 / 65 Nm. A versatile tool for fitters, builders and maintenance staff. Integrated LED light. Tool only, battery and a charger not included.



### Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
No load speed	0 - 550 / 0 - 2100 min <sup>-1</sup>
Max. fastening torque Hard/Soft	130 / 65 Nm
Torque setting	21
Max Torque	141 Nm
Max. Drilling Diameter in Wood	76 mm
Drilling Capacity Wood (Auger Bit)	50 mm
Drilling Capacity Wood (Self-feed bit)	76 mm
Max. Drilling Diameter in Steel	13 mm
Drilling Capacity Hole Saw	152 mm
Drill Chuck Capacity	1,5 - 13 mm
Sound Power Level (L <sub>WA</sub> )	88 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	80 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level, Drilling into metal	≤ 2,5 m/s <sup>2</sup>

**EAN 0088381739702**

Link to product - [www.makita.uk.com](http://www.makita.uk.com)






### User benefits

- LED light illuminates the work site
- Highly efficient and compact machine for professional use
- Battery protection system automatically shuts off power when the battery level is low
- Electronic overload protection protects the user and the device
- Compact and lightweight for reduced operator fatigue
- Electric brake for maximum productivity and increased operator safety
- Keyless chuck for easy bit installation and removal











# Related products

## Standard AC

<b>122C02-5</b> Grip Assembly		<b>251314-2 (2x)</b> Truss Head Screw M4*12, Td140D	
<b>346317-0</b> Belt Hook		<b>452947-8</b> Bitholder	
<b>784637-8</b> Screw Bit, Ph2 – S6, 45 Mm, Double			

## Optional AC

<b>251314-2 (2x)</b> Truss Head Screw M4*12, Td140D		<b>346317-0</b> Belt Hook	
<b>346449-3</b> Belt Hook		<b>452947-8</b> Bitholder	
<b>784637-8</b> Screw Bit, Ph2 – S6, 45 Mm, Double		<b>821550-0</b> Makpac case (2)	
<b>837916-4</b> MakPac (2) Inlay		<b>D-72833</b> Metal Drill Bit set HSS-Tin, 2 - 8 mm,	

## Other

User manual

Parts drawing