Reciprocating Saw LXT®

DJR187

18V • 0 – 3 000 min^{-1} • 32 mm

Efficient brushless reciprocating saw

An efficient brushless reciprocating saw for spark-free cutting of metal and demolition work for professional use. Two speed settings, stroke length of 32 mm and stroke rate of 0 – 2 800 min^{-1} with continuous control from the switch. Quick-release blade attachment.



Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Brushless Motor	✓
Strokes per Minute (SPM)	0 - 2300 / 3000 min^{-1}
Length of Stroke	32 mm
Max. Cutting Capacity in Wood (90°)	255 mm
Max. Cutting Capacity in Steel Pipe	130 mm
Sound Power Level (L_{WA})	95 dB(A)
Sound Pressure Level (L_{pA})	87 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level, Cutting Boards	16,5 m/s^2
Vibration Uncertainty (K Factor), Cutting Boards	1,5 m/s^2
Vibration Level, Cutting Wooden Beam	15,5 m/s^2

User benefits

- Tool-less blade change and shoe adjustment
- LED light illuminates the work site
- Wide hanging hook, e.g. for scaffolding
- eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- Battery protection system automatically shuts off power when the battery level is low
- Slim design with rubberised grip for comfort

Link to product - www.makitauk.com

Related products

Other

User manual

Parts drawing