

Slide Compound Mitre Saw

LS0816F

1,200 W, 216 mm, 5,000 min⁻¹

Model LS0816F is a 216mm (8-1/2") slide compound mitre saw.

Features and Benefits:

- Lock-off function
- LED job light
- Dust collection
- Double insulation
- Sub-base can be pulled out for more stable cutting
- Slide style sub fence (left side only)
- Soft grip



Technical specifications

Capacity 90°	65 x 305 mm
Max. kerf thickness of the saw blade	2,8 mm
Continuous Input Power 240V	1200 W
No load speed	5000 min ⁻¹
Capacity 45°	65 x 215 mm
Capacity 45° left	36 x 305 mm
Max. Bevel Range (Left)	47 / 2 °
Max. Mitre Range (Left)	47 / 47 °
Blade Diameter	216 mm
Bore Size (Arbor Diameter)	30 mm
Power Supply Cord	2,0 m
Sound Power Level (L _{WA})	102 dB(A)
Sound Pressure Level (L _{pA})	91 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²

EAN 0197050001610

Link to product - www.makita.uk.com

User benefits

- Double insulated
- High cutting capacity and dust extraction rate
- High dust extraction rate - Connects directly to Makita vacuum cleaner for a cleaner work area
- Carry handle for easy transportation



Related products

■ Optional AC

JM00000445

Uni Hex Key Wrench



■ Other

User manual

Parts drawing